

ECO R ULTRA

Analogue Radiator



- Maximum heat performance with minimal energy consumption
- Compact sizes from 660 - 2000W
- Simple to use analogic dial
- Snap switch ambient Thermostat
- Floor standing castors and wall bracket kit included
- Guarantee, 15 years on the body, 6 years on the electronics

Product Specification									
Reference	Elements	Power	Width	Height	Depth	Weight	Volts	Heats Room Size	
	Number	W	mm	mm	mm	Kg	V	Very Cold	Extra Cold
ECORU04	4	660	450	580	98	10.54	230	9.8m ²	9.4m ²
ECORU06	6	1000	610			14.16		13.8m ²	13.2m ²
ECORU08	8	1330	770			18.08		17.8m ²	17.0m ²
ECORU10	10	1670	930			21.58		21.8m ²	20.8m ²
ECORU12	12	2000	1090			25.74		25.8m ²	24.6m ²
Guarantee									
Body	15 Years								
Electronics	6 Years								
Radiator Material									
Body	New European aluminium with higher patent-protected performance. Die-cast aluminium with modern and efficient designs that favour natural convection.								
End Panels	Double lateral ABS VO end panels, made of self-extinguishing material.								
Control Panel	Fire-proof PC/ABC								
Heating Element	AISI-304 stainless steel armoured electrical resistance with low specific value and high heat performance								
Thermal Fluid	FARHOIL– Thermoconductor fluid with low specific value and high heat performance. Made exclusively for FARHO by SHELL.								
Safety Information									
Safety Heat Limiter	Yes								
Overheat Protection	Yes								
Certification									
Ecodesign	Yes								
CE	Yes								
IP Rating	IP24								